

Kindly replace the brief descriptions of Figs. 3-6 on page 7, line 12 to page 8, line 7 with the following paragraphs.

Fig. 3 is a perspective view of the jamb plate of the present invention with the first yoke in an ~~first~~, engaged [[,]] position and the second yoke in a ~~first~~, retracted [[,]] position.

Fig. 4 is a perspective view of the jamb plate of the present invention with the first yoke in an ~~a first~~, engaged [[,]] position and the second yoke in ~~a second~~, an engaged position.

Fig. 5 is a perspective view of the door plate and the jamb plate of the present invention with each of the first yoke and second yoke in a ~~second~~, retracted position.

Fig. 6 is a perspective view of the jamb plate and the door plate of a second embodiment of the present invention with the first yoke in an ~~a first~~, engaged [[,]] position and the second yoke in a ~~second~~, retracted [[,]] position.

Kindly replace the brief description of Fig. 9 on page 8, lines 15-17 with the following paragraph.

Fig. 9 is a ~~perspective~~ side view of an additional embodiment of the jamb plate and the door plate of the present invention ~~depicting an additional embodiment of the arm and second yoke.~~

Kindly insert the following brief description of Figs. 10 and 11 following the last line (line 17) of page 8 of the specification.

Fig. 10 is a side view of the jamb plate and door plate of the additional embodiment shown in Fig. 9, with the second yoke in an engaged position.

Fig. 11 is a side view of a tongue extending from the second yoke of the jamb plate, the tongue being optionally included as part of the second yoke of any of the disclosed embodiments of the invention.